



## SINGLE CEILING-CONCEALED SPLIT SYSTEMS

**NEW**

### HEAT PUMP VCSI TECHNOLOGY

- Variable Compressor Speed Inverter Technology
- Ozone-Friendly R-410A Refrigerant
- Significant Energy Savings (up to 30%)
- Auto Change Over between Cooling & Heating
- Extreme Quiet Operation - as low as 23dB(A)
- Ultra-thin profile - only 7-7/8 in. high**
- Adjustable ESP to meet different layouts
- Built-in High-Performance Drain Pump**
- Long Pipe Runs - Up to 100 ft.
- Refrigerant Pre-Charged
- 5-Year Parts Warranty
- 7-Year Compressor Warranty



Optional accessories available.  
Visit [www.mrslim.ca](http://www.mrslim.ca) for more information.



Model			SEZ-KD09NA ★ NEW	SEZ-KD12NA ★ NEW	SEZ-KD15NA ★ NEW	SEZ-KD18NA ★ NEW
Capacity (Rated)	Cooling	Btu/h	8,100	11,500	14,100	17,200
Capacity (Min ~ Max)		Btu/h	3,800 ~ 10,900	3,800 ~ 13,300	3,800 ~ 17,000	3,800 ~ 19,000
Capacity (Rated)	Heating	Btu/h	10,900	13,600	18,000	21,600
Capacity (Min ~ Max)		Btu/h	4,800 ~ 14,100	4,800 ~ 16,400	4,800 ~ 21,100	4,800 ~ 24,900
Power Consumption (Rated)	Cooling	W	670	920	1,170	1,380
	Heating	W	1,020	1,140	1,500	1,700
EER	Cooling		12.0	12.5	12.0	12.5
SEER	Cooling		15.0	16.0	15.5	17.5
HSPF (IV)	Heating		10.0	10.0	10.0	10.0
Capacity Control			Variable Speed Compressor (VCSI)	Variable Speed Compressor (VCSI)	Variable Speed Compressor (VCSI)	Variable Speed Compressor (VCSI)
Refrigerant			R-410A	R-410A	R-410A	R-410A
Power Supply	V, Phase, Hz		208/230, 1, 60	208/230, 1, 60	208/230, 1, 60	208/230, 1, 60
Moisture Removal	Pints/h		1.5	2.4	2.6	3.4
External Static Pressure	in. WG (Pa)		0.02-0.06-0.14-0.20 (5-15-35-50)	0.02-0.06-0.14-0.20 (5-15-35-50)	0.02-0.06-0.14-0.20 (5-15-35-50)	0.02-0.06-0.14-0.20 (5-15-35-50)
Airflow (Low-Med-Hi)	CFM Dry		194-247-317	247-317-388	353-441-529	423-529-635
Sound Indoor (Low-Med-Hi)	Cooling	dB(A)	23-26-30	23-28-33	30-34-37	30-34-38
Sound Outdoor	Cooling	dB(A)	46	49	49	54
Max. Fuse Size (Time Delay)	Indoor	A	15	15	15	15
	Outdoor	A	15	15	15	15
Min. Ampacity	Indoor	A	1.0	1.0	1.0	1.0
	Outdoor	A	12	12	12	14
Fan Speed Control			4 (Auto, Hi, Med, Low)	4 (Auto, Hi, Med, Low)	4 (Auto, Hi, Med, Low)	4 (Auto, Hi, Med, Low)
Air Filters (Washable)			PP Honeycomb fabric	PP Honeycomb fabric	PP Honeycomb fabric	PP Honeycomb fabric
Dimensions (H x W x D)	Indoor	in.	7-7/8 x 31-1/8 x 27-9/16	7-7/8 x 39 x 27-9/16	7-7/8 x 39 x 27-9/16	7-7/8 x 46-7/8 x 27-9/16
	Outdoor	in.	21-5/8 x 31-1/2 x 11-1/4	21-5/8 x 31-1/2 x 11-1/4	21-5/8 x 31-1/2 x 11-1/4	33-7/16 x 33-1/16 x 13
Weight	Indoor	lbs.	42	50	54	62
	Outdoor	lbs.	66	77	80	119
Pipe Size	Liq. X Gas	in.	1/4 x 3/8	1/4 x 3/8	1/4 x 1/2	1/4 x 1/2
Max. Height Difference		Ft.	40	40	40	50
Max. Pipe Length		Ft.	65	65	65	100
Outdoor Operating Range	Cooling		14 - 115°FDB	14 - 115°FDB	14 - 115°FDB	14 - 115°FDB
	Heating		14 - 75°FDB (13 - 65°FDB)	14 - 75°FDB (13 - 65°FDB)	14 - 75°FDB (13 - 65°FDB)	14 - 75°FDB (13 - 65°FDB)

All features may not apply to all models. Ask your Dealer for details.

★ THIS SYMBOL DENOTES AN ENERGY STAR CERTIFIED UNIT